

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) An agricultural tractor comprising:

an engine;

a transmission driven by the engine

a drive axle driven by the transmission, the drive axle including a central housing having left and right drive output members, left and right axle housings movably coupled to the central housing for vertical movement of the left and right axle housings relative to the central housing, left and right axle shafts rotatably carried by the left and right axle housings and left and right universal joints drivingly coupling the left and right drive output members to the left and right axle shafts respectively, the universal joint comprising a drive yoke at an outboard end of the drive output member, the drive yoke defining an outboard face, a first journal member coupled to the drive yoke for pivotal motion about a first joint pivot axis transverse to a longitudinal axis of the drive output member, the first joint pivot axis being inboard of the drive yoke outboard face, a coupling yoke joined to the first journal member for pivotal motion about a second joint pivot axis transverse to the longitudinal axis of the drive output member and transverse to the first joint pivot axis, a driven yoke at an inboard end of the axle shaft, the driven yoke defining an inboard face, a second journal member coupled to the second yoke for pivotal motion about a third joint pivot axis transverse to a longitudinal axis of the axle shaft, the third joint pivot axis being outboard of the driven yoke inboard face, and the second journal member being joined to the coupling yoke for pivotal motion about a fourth joint pivot axis transverse to the longitudinal axis of the axle shaft and transverse to the third joint pivot axis; and

left and right wheel and tire assemblies coupled to the left and right axle shafts respectively.

2. (Original) The agricultural tractor as defined by claim 1 further comprising left and right inboard final drives in the central axle housing whereby the left and right drive output members rotate at the same speed as the left and right axle shafts, respectively.

3. (Original) The agricultural tractor as defined by claim 2 wherein the output members are planet carriers of the inboard final drives.

4. (Original) The agricultural tractor as defined by claim 1 wherein the left and right wheel and tire assemblies are positioned at a 60 inch tread spacing.

5. (Original) The agricultural tractor as defined by claim 1 further comprising means for infinitely adjusting the position of the wheel and tire assemblies along the left and right axle shafts.

6. (Original) The agricultural tractor as defined by claim 5 wherein the left and right wheel and tire assemblies are positioned at a 60 inch tread spacing.

7. (Original) The agricultural tractor as defined by claim 6 wherein the central housing includes left and right inboard final drives.

8. (Currently Amended) The agricultural tractor as defined by claim 6 wherein the engine has a power rating of at least 75 kW (~~100 hp~~).

9. (Currently Amended) The agricultural tractor as defined by claim 6 wherein the engine has a power rating of at least 124 kW (~~165 hp~~).

10. (Cancelled)

11. (Currently Amended) The agricultural tractor as defined by claim ~~40~~ 1 wherein the left and right axle housings are each coupled to the central housing by left and right upper and lower control arms pivotally coupled to the central housing and the axle housings for movement of the axle housings relative to the central

housing and at least one spring member extending between the frame and the axle housing to resiliently transmit loads from the frame to the axle housings.

12. (Original) The agricultural tractor as defined by claim 11 wherein the spring member is a hydraulic cylinder and extendable rod coupled to the central housing and to the axle housing, the hydraulic cylinder being connected in a hydraulic circuit with at least one pressure accumulator.

13. (Original) The agricultural tractor as defined by claim 11 further comprising a rotary potentiometer to measure the rotary position of one of the control arms.

14. (Cancelled)

15. (Cancelled)

16. (Original) The agricultural tractor as defined by claim 1 wherein the left and right axle housings are mechanically separated from one another whereby one axle housing can move without causing the other axle housing to move through a mechanical coupling.

17. (Cancelled)

18. (Currently Amended) The agricultural tractor as defined by claim 47 1 wherein the outboard face of the drive yoke and the inboard face of the driven yoke are axially adjacent to one another.

19. (Currently Amended) The agricultural tractor as defined by claim 47 1 wherein the outboard face of the drive yoke and the inboard face of the driven yoke are axially spaced less than one inch from one another.

20. (Currently Amended) The agricultural tractor as defined by claim 47 1 wherein the first journal member is an annular member surrounding a hub of the central housing.

21. (Currently Amended) The agricultural tractor as defined by claim 47 1 wherein the second journal member is an annular member surrounding a hub of the axle housing.

22. (Currently Amended) The agricultural tractor as defined by claim 47 1 further comprising inner bearings carried by a hub in the central housing and supporting the drive output member therein, the inner bearings extending axially outward beyond the first and second joint pivot axes; and  
outer bearings carried by a hub in the axle housing and supporting the axle shaft therein, the outer bearings extending axially inward beyond the third and fourth joint pivot axes.

23. (Cancelled)

24. (Cancelled)

25. (Cancelled)

26. (Currently Amended) An agricultural tractor comprising:  
a frame;  
an engine;  
a transmission driven by the engine;  
a drive axle assembly driven by the transmission, the axle assembly including a differential case having left and right planetary final drives, the final drives having an output member, left and right inner suspension housings fixed to the differential case, left and right upper and lower control arms pivotally coupled to the inner suspension housings and extending outward to distal ends, the control arms being coupled to the inner suspension housings by pins that define upper and lower pivot axes, and, left and right axle housings pivotally coupled to the distal ends of the

control arms for up and down movement of the axle housings relative to the inner suspension housings, the axle housings being coupled to the distal ends of the control arms by an upper ball joint and a lower ball joint, left and right axle shafts rotatably carried by the left and right axle housings, left and right universal joints drivingly coupling the output members of the left and right final drives to the left and right axle shafts respectively, and left and right spring members extending between the left and right inner suspension housings and the left and right axle housings to resiliently transmit loads from the frame to the axle housings, left and right connecting links extending between the left and right inner suspension housings and left and right axle housings to prevent rotation of the left and right axle housings about left and right upright axes defined by the left and right upper and lower ball joints; and

left and right wheel and tire assemblies coupled to the left and right axle shafts respectively.

27. (Original) The agricultural tractor as defined by claim 26 wherein the left and right wheel and tire assemblies are located on the axle shafts to provide a 60 inch tread width.

28. (Original) The agricultural tractor as defined by claim 26 wherein the left and right wheel and tire assemblies are adjustable in position along the left and right axle shafts.

29. (Original) The agricultural tractor as defined by claim 26 wherein the differential case and the left and right inner housings are rigidly fixed to and part of the frame.

30. (Cancelled)

31. (Cancelled)

32. (Cancelled)

33. (Cancelled)

34. (Original) The agricultural tractor as defined by claim 26 wherein the left and right spring members include hydraulic cylinders coupled in a hydraulic circuit to one or more pressure accumulators.

35. (Cancelled)

36. (Cancelled)

37. (Cancelled)

38. (Cancelled)

39. (Cancelled)

40. (Cancelled)

41. (Cancelled)

42. (Cancelled)

43. (Cancelled)

44. (Currently Amended) A suspended drive axle for a work vehicle comprising:

a differential case having left and right planetary final drives, the final drives having each having an output member;

left and right inner suspension housings fixed to the differential case;

left and right upper and lower control arms pivotally carried by the inner suspension housings and extending outward to distal ends, the control arms being coupled to the inner suspension housings by pins that define upper and lower pivot

axes, the axle housings being coupled to the distal ends of the control arms by an upper and a lower ball joint;

left and right axle housings pivotally coupled to the distal ends of the control arms for up and down movement of the axle housings relative to the inner suspension housings;

left and right connecting links extending between the left and right inner suspension housings and left and right axle housings to prevent rotation of the left and right axle housings about left and right upright axes defined by the left and right upper and lower ball joints;

left and right axle shafts rotatably carried by the left and right axle housings;

left and right universal joints drivingly coupling the output members of the left and right final drives to the left and right axle shafts respectively; and

left and right spring members extending between the left and right inner suspension housings and the left and right axle housings to resiliently transmit loads therebetween.

45. (Cancelled)

46. (Cancelled)

47. (Cancelled)

48. (Cancelled)

49. (Original) The drive axle as defined by claim 44 wherein the left and right spring members include hydraulic cylinders coupled in a hydraulic circuit to one or more pressure accumulators.

50. (Original) The drive axle as defined by claim 44 wherein each universal joint comprises:

an drive yoke at an outboard end of the drive output member;  
an driven yoke at in inboard end of the axle shaft;

inboard and outboard journal members pivotally coupled to the drive and driven yokes respectively;

a coupling yoke pivotally coupled to both the inboard and outboard journal members;

the inboard and outboard journal members and the coupling yoke being positioned radially outward of the drive yoke and driven yoke wherein the drive yoke and driven yoke are axially adjacent one another.

51. (Withdrawn)

52. (New) An agricultural tractor comprising:

an engine;

a transmission driven by the engine

a drive axle driven by the transmission, the drive axle including a central housing having left and right drive output members, left and right axle housings movably coupled to the central housing for vertical movement of the left and right axle housings relative to the central housing, left and right axle shafts rotatably carried by the left and right axle housings and left and right universal joints drivingly coupling the left and right drive output members to the left and right axle shafts respectively, the universal joint comprising, a drive yoke at an outboard end of the drive output member, a driven yoke at an inboard end of the axle shaft, inboard and outboard journal members pivotally coupled to the drive and driven yokes respectively, a coupling yoke pivotally coupled to both the inboard and outboard journal members, the inboard and outboard journal members and the coupling yoke being positioned radially outward of the drive yoke and driven yoke; and,

left and right wheel and tire assemblies coupled to the left and right axle shafts respectively.

53. (New) The agricultural tractor as defined by claim 52 wherein the central housing has an axially extending bearing hub supporting the drive output member, and the inboard journal member radially surrounds the bearing hub.

54. (New) The agricultural tractor as defined by claim 52 wherein the axle



Application No. 10/655,186  
Amendment Dated 5 January 2005  
Reply to Office Action of 6 October 2004

housing has an axially extending bearing hub supporting the axle shaft, and the outboard journal member radially surrounds the bearing hub.